



SALAD SPINNER SERIES

MANUAL SALAD SPINNER E20 SC

Ref : E004



ADVANTAGES

- Certified to NSF / ANSI 2-2009: **North American Health standard certifying that the product meets strict requirements of quality and safety.**
- More hygienic thanks to its sealed cover : no water or bacteria retention.
- Fast and efficient, it respects the product's fragility.
- Heavy duty construction for an intensive daily use. 100 % watertight to avoid water effusion.
- Outside container, top and inner basket in Polypropylene (Food-safe plastic).
- Aluminum handle.
- Antibacterial incorporated (biocide treated), complies with the HACCP requirements.



ACCESSORY

Ref. AC019



Stabilising base: base with the suction pads. For increased stability.



USE

Indispensable to prepare high volume of salads.

IMPORTANT : when turning the handle, start off slowly. Never stop the unit from spinning by grabbing the handle.

Capacity : 20 L.



MAINTENANCE

To clean, simply remove the top and inner basket from the outside container. Wash all three components thoroughly with a mild liquid soap.

Rinse with hot water as to remove all soap residues.

Do not put in the dishwasher.



TECHNICAL DATA

TOTAL HEIGHT	500 mm
DIAMETER	430 mm
ACTUAL WEIGHT	3,6 kg

www.dynamicmixers.com

Dynamic - 518 rue Léo Baekeland BP57 - 85290 Mortagne sur Sèvre

Tel : +33 (0)2 51 63 02 72 • E-mail : export@dynamicmixers.com

Follow us on social networks!



TECHNICAL SHEET

Parts list	Code
Waterproof seal 14 x 24 x 7	0644
Waterproof seal 25 x 37 x 6	0645
O. Ring	0646
Screws TBF 3.9 x 14	079958
Outside basket	2801
Perforated drive gear + pin	2806
Large gear	2807
Small gear	2808
Axle for outside basket	2810
Pin for large gear	2811
Axle for drive & small gear	2813
Axle	2814
Set of gears (2806, 2807, 2808, 2811, 2822)	2815.2
Handle only	2820
Small cover (w/ o handle & drive gear)	2821
Output small gear	2822
Equipped cover (O. Ring + Waterproof seal)	2823
Coupling sleeve	2824
Inside basket	2825
Small cover with handle & gear	2826
Complete cover	2827
Plate + screws (3)	2828
Screws (4)	9014



